





Rhino HT-CER 52 is a ceramic RAIN (UHF) RFID tool tag offered by SIVA with an Alien Higgs 3 chip for good read range performance on metallic surfaces. The tag is small in size and hence ideal for tool tracking in an industrial environment and also tracking medical tools used in healthcare. Customer specific encoding of EPC is also offered.

PHYSICAL SPECIFICATION	
Tag Material	Ceramic
Tag Dimensions	5.0 x 2.5 mm x T: 2 mm 0.19 x 0.09 in x T:0.07in
Mounting Methods	Adhesive
Weight	0.3 g
Delivery Format	Single Pieces



RF SPECIFICATION	
Mode of Operation	Passive
Device Type	Ceramic Tag
Air Interface Protocol	EPC Class1 Gen2, ISO18000-6C
Operational Frequency	ETSI: 865-868MHz FCC: 902-928MHz
IC Type	Alien Higgs 3
Memory Configuration	EPC 96bits , USER 512bits, TID64bits
Write Cycle Endurance	100,000
Data Retention	Upto 50 years
Applicable Surface Materials	Metallic surfaces
Read Range (Fixed Reader)	On metal 30cm
Read Range (Handheld Reader)	On metal 20cm

ENVIRONMENTAL RESISTANCE

Operating Temperature	-40°C to +85°C / -40°F to +185°F
Withstands Exposure To	-40°C to +150°C / -40°F to +302°F
Peak Temperature	+150°C / +302°F
Recommended Application Temperature	+10°C to +38°C / 50°F to +100.4°F
Water Resistance (IP Rating)	IP68
Ideal Storage Condition	-40°C to +150°C / -40°F to 302°F
Expected Lifetime	Years in normal operating conditions

PERSONALIZATION OPTIONS

Pre-encoding

- Customer specific encoding of EPC

ORDER INFORMATION

Part Number

- RF.HT-CER.52.ETSI.H3
- RF.HT-CER.52.FCC.H3

* The indicated read range values are measured in our laboratory testing environment, where antennas with optimum directivity are used with maximum allowed operating power. Different surface materials and environments may exhibit different results.



Version : 170221.01